





Series RX48 | Removable lids along outer radius

| Removable lids along outer radius | <i>Bi</i> [mm] | <i>Ba</i> [mm] | <i>R</i> Bending radii [mm] | Weight [kg/m] |
|-----------------------------------|-------------------|-------------------|---|------------------|
| RX48. <i>120</i> . <i>R.0</i> | 120 | 147,6 | 120 150 175* 200* 225* 250* 275* 300* 325* | ≈ 2,76 |

*Radius available upon request, please consult igus® for delivery time!

Supplement Part No. with required radius (*R*). Example: RX48.**120.120.0**

Dimensions




| <i>R</i> | 120 | 150 | 175* | 200* | 225* | 250* | 275* | 300* | 325* |
|----------|------------|------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|
| <i>H</i> | 324 | 384 | 434 | 484 | 534 | 584 | 634 | 684 | 734 |
| <i>D</i> | 234 | 264 | 289 | 314 | 339 | 364 | 389 | 414 | 439 |
| <i>K</i> | 475 | 570 | 650 | 725 | 805 | 885 | 960 | 1040 | 1120 |

The required clearance height: $H_F = H + 50$ mm (with 0,5 kg/m fill weight)


*Radius available upon request, please consult igus® for delivery time!

Mounting brackets, flange | Polymer locking, two-piece



Flange mounting brackets, locking



| Width Index | Part No. full set with tie-wrap plates | Part No. full set without tie-wrap plates | Number of teeth |
|----------------|---|--|--------------------|
| .120. ▶ | upon request | RX481.120.12 | upon request |
| | | | |
| | | | |
| | | | |



| RX481.120.12 A Part No. structure |
|--|
| A...must be indicated on preassembled configurations |
| Full set |
| Width Index |
| Mounting bracket for selected width index |

Strain relief e.g. clamps, tie-wrap plates, nuggets and plug-in clips are available from stock. The complete chainfix range with order options ▶ from page 656

Interior separation



Vertical separation - slotted separators:

RX48.1 (central positioning)

RX48.2 (lateral positioning)

Vertical separation of the large filling space by cable-friendly, polymer separators. Due to their slots, basic vertical/horizontal shelving arrangements are possible. In the standard configuration separators are assembled every 2nd e-chain® link!

Horizontal separation

Full-width shelf locks safely into separators on both ends, fixed width possible. Separators can be moved freely over the shelf in horizontal direction. Can be used at one height.

Lockable full-width shelves

| Width X [mm] | unassembled | assembled | Width X [mm] | unassembled | assembled |
|--------------|-------------|-----------|--------------|-------------|-----------|
| 034 | 520.34 | 521.34 | 094 | 520.94 | 521.94 |
| 064 | 520.64 | 521.64 | 124 | 520.124 | 521.124 |



Hot Chips up to 850°C

RX e-tubes that repel hot chips, up to 850°C. Some applications, depending on amount and size of the chips, can burn or melt the surface. That is no longer the case with the igus® "igumid HT" material. Order example: **Part No. RX48.120.120.0.HT** Delivery time upon request.

More information ► www.igus.eu/HT




Optional: Support tray tool kit.

For support of the lower run.

- Open trough design for safe guidance of the RX e-tube
- Chips can fall through
- In 2 lengths available

More information ► www.igus.eu/RX48



Polymer strain relief block.

For RX e-tubes flange mounting brackets.

- Tight strain relief block according to your specifications
- Fast assembly by standard screw connection
- Can be mounted in the mounting bracket

More information ► www.igus.eu/RX48



With the extreme tight igus® RX e-tube and the harnessed chainflex®-cables, the lifetime of this woodworking machine could be considerably increased. Because of dust and dirt, most after one month previously installed cables failed